

POLYLACTIC ACID COMPOSITION, ITS PRODUCTION AND MOLDED PRODUCT FROM THE COMPOSITION

Publication number: JP10176039

Publication date: 1998-06-30

Inventor: HIRAI YOSHIAKI; HORIKAWA YUKIO; KIMURA YOSHIHARU

Applicant: KANEBO LTD

Classification:

- international: C08K5/07; C08G63/08; C08G63/64; C08G63/78; C08G63/84; C08L67/04; C08L101/16; C08K5/00; C08G63/00; C08L67/00; C08L101/00; (IPC1-7): C08G63/08; C08G63/64; C08G63/78; C08G63/84; C08K5/07; C08L67/04

- European:

Application number: JP19970110169 19970410

Priority number(s): JP19970110169 19970410; JP19960297506 19961018

[View INPADOC patent family](#)

[View list of citing documents](#)

[Report a data error here](#)

Abstract of **JP10176039**

PROBLEM TO BE SOLVED: To obtain a polylactic acid composition having high molecular weight and excellent heat stability with a small lowering of molecular weight in molding and capable of giving a molded product having high strength by containing a specific polylactic acid-based copolymer and tris(acetylacetonato) aluminum at a specific ratio. **SOLUTION:** This composition contains (A) a polylactic acid-based copolymer as a copolymer of (i) L- and/or D-lactic acid and (ii) a segment derived from at least one kind of compound selected from the group consisting of polyalkylene glycols, polyhydric alcohols, hydroxycarboxylic acids, aliphatic polyesters, lactones, lactams and cyclic carbonates [preferably a copolymer of the component (i) and polyethylene glycol] and (B) tris(acetylacetonato) aluminum in an amount of 0.075-2.0mol% based on a lactic acid unit of the component A. The component A is obtained by performing melt ring-opening polymerization of lactide as a cyclic dimer of lactic acid with the component (ii) by using the component B in an amount of 0.15-4.0mol% based on the lactide as a catalyst.

Data supplied from the *esp@ccenet* database - Worldwide